




OPERATORS MANUAL

FOR ROTAX® ENGINE TYPE 912 SERIES

Ref. No.: **OM-912**



ROTAX® **912 ULS 3** WITH OPTIONS

 **WARNING**

Before starting the engine, read the Operator's Manual, as it contains important safety relevant information. Failure to do so may result in personal injuries including death. Consult the original equipment manufacturers handbook for additional instructions!

These technical data and the information embodied therein are the property of BRP-Rotax GmbH&Co. KG, Austria, acc, BGBl 1984 no. 448, and shall not, without prior written permission of BRP-Rotax GmbH&Co. KG, be disclosed in whole or in part to third parties. This legend shall be included on any reproduction of these data, in whole or in part. The Manual must remain with the engine/aircraft in case of sale.

Copyright 2006 © - all rights reserved.

ROTAX[®] is a trade mark of BRP-Rotax GmbH&Co. KG. In the following document the short form of BRP-Rotax GmbH&Co. KG = BRP-Rotax is used.

Other product names in this documentation are used purely for ease of identification and may be trademarks of the respective company or owner.

Approval of translation has been done to best knowledge and judgement - in any case the original text in german language is authoritative.

1)	Table of contents	1-3
2)	Index.....	2-1
3)	Introduction	3-1
	3.1) Remarks.....	3-1
	3.2) Engine serial number	3-1
4)	Safety	4-1
	4.1) Repeating symbols.....	4-1
	4.2) Safety information	4-2
	4.3) Technical documentation	4-5
5)	Index of pages.....	5-1
6)	List of amendments	6-1
7)	Description of design	7-1
	7.1) Type description	7-2
	7.2) Denomination of cylinders:	7-3
8)	Technical data	8-1
	8.1) Dimensions	8-1
	8.2) Weights.....	8-1
	8.3) Fuel consumption.....	8-2
	8.4) Direction of rotation	8-2
9)	Description of systems	9-1
	9.1) Cooling system	9-1
	9.2) Fuel system	9-2
	9.3) Lubrication system.....	9-3
	9.4) Electric system	9-4
	9.5) Propeller gearbox	9-5
	9.5.1) Hydr. governor for const. speed propeller, vacuum pump:.....	9-6
10)	Operating instructions	10-1
	10.1) General limits of operation	10-1
	10.1.1) Operating speeds and limits (912 UL / A / F).....	10-1
	10.1.1.1) Performance graphs for stand. conditions (ISA) ..	10-3
	10.1.1.2) Performance graph for non-standard conditions...	10-4
	10.1.2) Operating speeds and limits (912 ULS / S).....	10-5
	10.1.2.1) Performance graphs for stand. conditions (ISA) ...	10-7
	10.1.2.2) Performance graph for non-standard conditions...	10-8
	10.2) Operating media	10-9
	10.2.1) Coolant.....	10-9
	10.2.2) Fuel.....	10-10
	10.2.3) Lubricants	10-11
	10.3) Standard operation.....	10-13
	10.3.1) Daily checks.....	10-13
	10.3.2) Before engine start.....	10-14
	10.3.3) Pre-flight checks	10-15
	10.3.4) Engine start.....	10-16
	10.3.5) Prior to take-off	10-17
	10.3.6) Take-off.....	10-17

10.3.7)	Cruising	10-18
10.3.8)	Engine shut-off	10-18
10.3.9)	Cold weather operation	10-18
10.4)	Abnormal operation	10-20
10.4.1)	Engine stop - Start during flight	10-20
10.4.2)	Exceeding of max. admissible engine speed	10-20
10.4.3)	Exceeding of max. admissible cyl. head temperature	10-20
10.4.4)	Exceeding of max. admissible oil temperature	10-20
10.4.5)	Oil pressure below minimum - during flight	10-20
10.4.6)	Oil pressure below minimum - on ground	10-20
11)	Checks	11-1
11.1)	Engine preservation	11-1
12)	Trouble shooting	12-1
12.1)	Reporting	12-4
13)	Authorized Distributors for ROTAX® Aircraft Engines.....	13-1

2) Index

A

Abnormal operation 10-20
Acceleration (912 UL / A / F) 10-1
Acceleration (912 ULS / S) 10-5
AVGAS 100LL 10-10

C

Carburetor 10-14
Certification 7-2
Check of hydraulic propeller governor 10-17
Checks 11-1
Cold start 10-18
Cold weather operation 10-18
Configuration 7-2
Cooling system 9-1
Cruising 10-18
Cylinder head temperature (912 ULS / S) 10-5

D

Daily checks 10-13
Denomination of cylinders 7-3
Description of design 7-1
Description of systems 9-1
Dimensions 8-1
Direction of rotation 8-2
Documentation (technical) 4-5

E

Electric system 9-4
Engine preservation 11-1
Engine serial number 3-1
Engine shut-off 10-18
Engine start 10-16
Engine start, operating temperature (912 ULS / S) 10-5
Equipment 8-1
Exceeding of max. admissible cyl. head temperature 10-20
Exceeding of max. admissible engine speed 10-20
Exceeding of max. admissible oil temperature 10-20
Exhaust system 10-14

F

Fuel 10-10
Fuel consumption 8-2
Fuel pressure (912 UL / A / F) 10-2
Fuel pressure (912 ULS / S) 10-6
Fuel system 9-2

H

Hydr. governor for const. speed propeller 9-6

I

Ignition check 10-17
Ignition unit 9-4
Index of pages 5-1
Introduction 3-1

L

List of amendments 6-1
Lubricants 10-11
Lubrication system 9-3

M

magneto side 7-3

O

Oil consumption 10-12
Oil pressure (912 UL / A / F) 10-1
Oil pressure (912 ULS / S) 10-5
Oil pressure below minimum - during flight 10-20
Oil pressure below minimum - on ground 10-20
Oil specification 10-11
Oil temperature (912 UL / A / F) 10-1
Oil temperature (912 ULS / S) 10-5
Oil viscosity 10-12
Operating media 10-15
Operating speeds and limits (912 UL / A / F) 10-1
Operating speeds and limits (912 ULS / S) 10-5
Overload clutch 9-5

P

Performance (ISA) (912 UL / A / F) 10-1
Performance (ISA) (912 ULS / S) 10-5
Performance data 10-4, 10-8
Performance graphs for stand. conditions (ISA) 10-3, 10-7
power take-off side 7-3
Pre-flight checks 10-15
Propeller gearbox 9-5
Propeller governor 9-6

R

Remarks 3-1
Repeating symbols 4-1
Reporting 12-4

S

Safety 4-1
Safety information 4-2
Speed (912 UL / A / F) 10-1
Speed (912 ULS / S) 10-5
Symbols 4-1

T

Table of lubricants 10-12
Take-off 10-17
Technical data 8-1
Technical documentation 4-5
Throttle response 10-17
Trouble shooting 12-1
Type 7-2
Type description 7-2

V

Vacuum pump 9-6

W

Warming up period 10-17
Weights 8-1

3) Introduction

Congratulations on your decision to purchase a ROTAX aircraft engine.

Before operating the engine, carefully read this Operator's Manual. The Manual provides you with basic information on the safe operation of the engine.

If any passages of the Manual are not clearly understood or in case of any questions, please, contact an authorized Distribution- or Service Center for ROTAX aircraft engines.

We wish you much pleasure and satisfaction flying your aircraft with this ROTAX engine.

3.1) Remarks

The purpose of this Operator's Manual is provided to familiarize the owner/ user of this aircraft engine with basic operating instructions and safety information.

For more detailed maintenance, safety and flight information, consult the documentation provided by the aircraft manufacturer and dealer.

For further information on maintenance and spare parts service, contact the nearest ROTAX distribution Center (see Chapter 13).

3.2) Engine serial number

On all enquiries or parts orders, always indicate the engine serial number, as the manufacturer makes modifications to the engine for product improvement. The engine serial number should always be used when ordering parts to ensure correct part selection prior to shipment.

The engine serial number is located on the top of the crankcase, magneto side. See fig. 2.

NOTES

4) Safety

Although the mere reading of these instructions will not eliminate a hazard, the understanding and application of the information herein will promote the proper use of the engine.

The information and components-/system descriptions contained in this Operator's Manual are correct at the time of publication. ROTAX however, maintains a policy of continuous improvement of its products without imposing upon itself any obligation to install them on its products previously manufactured.

ROTAX reserves the right at any time to discontinue or change specifications, designs, features, models or equipment without incurring obligation.

The illustrations in this Manual show the typical construction. They may not represent in full detail or the exact shape of the parts which have the same or similar function.

Specifications are given in the SI metric system with the USA equivalent in parenthesis. Where precise accuracy is not required, some conversions are rounded off for easier use.

This document has been translated from the German language and the original German text shall be deemed authoritative.

4.1) Repeating symbols

This Manual uses the following symbols to emphasize particular information:

- ▲ **WARNING:** Identifies an instruction which, if not followed, may cause serious injury including the possibility of death.
- **CAUTION:** Denotes an instruction which, if not followed, may severely damage the engine or other component.
- ◆ **NOTE:** Indicates supplementary information which may be needed to fully complete or understand an instruction.

4.2) Safety information

- ▲ **WARNING:** Never fly the aircraft equipped with this engine at locations, airspeeds, altitudes, or other circumstances from which a successful no-power landing cannot be made, after sudden engine stoppage.

Unless correctly equipped to provide enough electrical power for night VFR (according latest requirement as ASTM), the ROTAX 912 UL/ULS/ULSFR is restricted to DAY VFR only.

- This engine is not suitable for acrobatics (inverted flight, etc.).
- This engine shall not be used on rotorcrafts with an in-flight driven rotor (e.g. helicopters).
- It should be clearly understood that the choice, selection and use of this particular engine on any aircraft is at the sole discretion and responsibility of the aircraft manufacturer, assembler and owner/user.
- Due to the varying designs, equipment and types of aircraft, ROTAX grants no warranty or representation on the suitability of its engine's use on any particular aircraft. Further, ROTAX grants no warranty or representation of this engine's suitability with any other part, component or system which may be selected by the aircraft manufacturer, assembler or user for aircraft application.
- Whether you are a qualified pilot or a novice, complete knowledge of the aircraft, its controls and operation is mandatory before venturing solo. Flying any type of aircraft involves a certain amount of risk. Be informed and prepared for any situation or hazard associated with flying.

A recognized training program and continued education for piloting an aircraft is absolutely necessary for all aircraft pilots. Make sure you also obtain as much information as possible about your aircraft, its maintenance and operation from your dealer.

- You should be aware that any engine may seize or stall at any time. This could lead to a crash landing and possible severe injury or death. For this reason, we recommend strict compliance with the maintenance and operation and any additional information which may be given to you by your dealer.
- Respect all government or local rules pertaining to flight operation in your flying area. Fly only when and where conditions, topography, and airspeeds are safest.
- Select and use proper aircraft instrumentation. This instrumentation is not included with the ROTAX engine package. Only approved instrumentation may be installed.

d02820.fm

- Before flight, ensure that all engine controls are operative. Make sure all controls can be easily reached in case of an emergency.
- Unless in a run up area, never run the engine with the propeller turning while on the ground. Do not operate engine if bystanders are close.
- In the interest of safety, the aircraft must not be left unattended while the engine is running.
- Keep an engine log and respect engine and aircraft maintenance schedules. Keep the engine in top operating condition at all times. Do not operate any aircraft which is not properly maintained or has engine operating irregularities which have not been corrected.

Since special tools and equipment may be required, engine servicing should only be performed by an authorized ROTAX engine dealer or a qualified trained mechanic approved by the local airworthiness authority.

- To eliminate possible injury or damage, ensure any loose equipment or tools are properly secured before starting the engine.
- When in storage protect the engine and fuel system from contamination and exposure.
- Certain areas, altitudes and conditions present greater risk than others. The engine may require carburetor recalibration or humidity or dust/sand preventative equipment, or additional maintenance may be required.

Consult your aircraft dealer or manufacturer and obtain the necessary information, especially before flying in new areas.

- Never operate the engine and gearbox without sufficient quantities of lubricating oil.
- Periodically verify level of coolant.
- Never exceed maximum rated r.p.m. Allow the engine to cool at idle for several minutes before turning off the engine.
- This engine may be equipped with an Airborne vacuum pump. The safety warning accompanying the vacuum pump must be given to the owner/operator of the aircraft into which the vacuum pump is installed.

NOTES

4.3) Technical documentation

These documents form the instructions for continued airworthiness of ROTAX aircraft engines:

- Installation Manual 912 F
- Installation Manual 912 A
- Installation Manual 912 UL
- Installation Manual 912 S
- Operators Manual
- Maintenance Manual 912 Series (Line and Heavy Maintenance)
- Overhaul Manual 912 A / F
- Illustrated Parts Catalog 912 A / F / S / UL / ULS / ULSFR
- Alert Service Bulletins
- Service Bulletins
- Service Instructions
- Service Letters

Any reference to a document refers to the latest edition issued by ROTAX if not stated otherwise.

- ◆ **NOTE:** The status of Manuals can be determined by checking the table of amendments of the Manual. The 1st column of this table is the revision status. Compare this number to that listed on the ROTAX WebSite: www.rotax-aircraft-engines.com. Updates and current revisions can be downloaded for free.

The information given in the are based on data and experience that are considered applicable for professionals under normal conditions.

The fast technical progress and variations of installation might render present laws and regulations inapplicable or inadequate.

The illustrations in this Manual are mere sketches and show a typical arrangement. They may not represent the actual part in all its details but depict parts of the same or similar function. Therefore deduction of dimensions or other details from illustrations is not permitted.

All necessary documentation is available from the ROTAX Distribution- and Service Centers (see Chapter 13).

- ◆ **NOTE:** The Illustrations in this Operator's Manual are stored in a graphic data file and are provided with a consecutive irrelevant number.

This number (e.g. 00277) is of no significance for the content.

5) Index of pages

Chapter	Page	Date	Chapter	Page	Date
	cover page		10	10-1	02 01 2008
1	1-2	01 01 2007		10-2	02 01 2008
	1-3	01 01 2007		10-3	01 01 2007
	1-4	01 01 2007		10-4	01 01 2007
2	2-1	01 01 2007		10-5	01 01 2007
	2-2	01 01 2007		10-6	02 01 2008
3	3-1	01 01 2007		10-7	01 01 2007
	3-2	01 01 2007		10-8	01 01 2007
4	4-1	01 01 2007		10-9	01 01 2007
	4-2	02 01 2008		10-10	01 01 2007
	4-3	01 01 2007		10-11	01 01 2007
	4-4	01 01 2007		10-12	01 01 2007
	4-5	01 01 2007		10-13	02 01 2008
	4-6	01 01 2007		10-14	02 01 2008
5	5-1	02 01 2008		10-15	02 01 2008
	5-2	01 01 2007		10-16	01 01 2007
6	6-1	02 01 2008	11	10-17	01 01 2007
	6-2	01 01 2007		10-18	01 01 2007
7	7-1	01 01 2007	12	10-19	01 01 2007
	7-2	02 01 2008		10-20	01 01 2007
	7-3	01 01 2007		11-1	01 01 2007
	7-4	01 01 2007		11-2	01 01 2007
8	8-1	01 01 2007	13	12-1	01 01 2007
	8-2	01 01 2007		12-2	01 01 2007
9	9-1	01 01 2007		12-3	01 01 2007
	9-2	01 01 2007		12-4	01 01 2007
	9-3	01 01 2007		12-5	01 01 2007
	9-4	01 01 2007		12-6	01 01 2007
	9-5	01 01 2007		13-1	02 01 2008
	9-6	01 01 2007		13-2	02 01 2008
				13-3	02 01 2008
				13-4	01 01 2008
				rear page	

d03929.fm

NOTES

6) List of amendments

Approval*

The technical content is approved under the authority
of DOA Nr. EASA.21.J.048.

Currt no.	Chapter	Pages	Date of modification	Note of approval	Date of approval by authority	Date of insertion	Marks/Signature
0	1 to 13	all	01 01 2007	DOA*			
1	4	4-2	02 01 2008	DOA*			
1	5	5-1	02 01 2008	DOA*			
1	6	6-1	02 01 2008	DOA*			
1	7	7-2	02 01 2008	DOA*			
1	10	10-1	02 01 2008	DOA*			
		10-2	02 01 2008	DOA*			
		10-6	02 01 2008	DOA*			
		10-13	02 01 2008	DOA*			
		10-14	02 01 2008	DOA*			
		10-15	02 01 2008	DOA*			
1	13	13-1	02 01 2008	DOA*			
		13-2	02 01 2008	DOA*			
		13-3	02 01 2008	DOA*			

NOTES

7) Description of design

4-stroke, 4 cylinder horizontally opposed, spark ignition engine, one central cam-shaft - push-rods - OHV

Liquid cooled cylinder heads

Ram air cooled cylinders

Dry sump forced lubrication

Dual breakerless capacitor discharge ignition

2 constant depression carburetors

mechanical fuel pump

Prop drive via reduction gear with integrated shock absorber and overload clutch

◆ NOTE: The overload clutch is installed on all **serial production** aircraft engines which are certified and on non-certified aircraft engines of the configuration 3.

Electric starter (12V 0,6 kW)

Electric starter (12V 0,9 kW), **optional**

Integrated AC generator with external rectifier-regulator (12V 20A DC)

External alternator (12V 40A DC), **optional**


Vacuum pump: (only for A1, A2 and A4 possible), **optional**

Hydraulic constant speed propeller governor: (for A3 only), **optional**

7.1) Type description

e.g. ROTAX 912 A 2

◆ NOTE: The type designation is of the following composition.




Type:	912	...	4-cyl. horizontalle opposed, normal aspirated engine
Certification:	A	...	certified to JAR 22 (TC No. EASA.E.121)
	F, S	...	certified to FAR 33 (TC No. E00051 EN) JAR-E (TC No. EASA.E.121)
	UL, ULS	...	non-certified aircraft engines
Configuration:	1	...	Prop shaft with flange for fixed prop, P.C.D 100 mm

◆ NOTE: This configuration is not available any longer and will be replaced by configuration 2.


- 2 ... Prop shaft with flange for fixed prop, P.C.D 75 mm, P.C.D 80 mm and 4" P.C.D
- 3 ... propeller P.C.D. 75 mm, P.C.D. 80 mm, P.C.D. 4" and drive for hydraulic governor for constant speed propeller
- 4 ... Prop flange for fixed pitch propeller P.C.D. 75 mm, P.C.D. 80 mm, P.C.D. 4" and prepared for retrofit of a hydraulic governor for constant speed propeller

d02823.fm

7.2) Denomination of cylinders:




00337



00334

d03931.fm



Front view

- | | |
|---|--|
| (1) engine serial number | (6) exhaust flange |
| (2) CD carburetor | (7) external alternator |
| (3) propeller gear box | (8) vacuum pump or hydraulic governor for constant speed propeller |
| (4) electric starter | |
| (5) expansion tank with excess pressure valve | |

8) Technical data

8.1) Dimensions

Description	912 UL / A / F	912 UL / ULS
Bore	79,5 mm (3,13 in)	84 mm (3,31 in)
Stroke	61 mm (2,40 in)	61 mm (2,40 in)
Displacement	1211 mm ³ (73,9 in ³)	1352 mm ³ (82,5 in ³)
Compression ratio.	9,0 : 1	10,5 : 1

8.2) Weights

◆ **NOTE:** The stated weights are dry weights (without operating fluids)

with: electric starter, carburetors, internal generator, ignition unit and oil tank

without: exhaust system, radiator, airbox

Weight in kg (lb)	912 UL	912 A	912 F	912 ULS	912 S
Configuration 2/4	57,1 (126) with overload clutch	57,1 (126)	57,1 (126)	58,3 (128) with overload clutch	58,3 (128)
	55,4 (122) without clutch			56,6 (125) without clutch	
Configuration 3	59,8 (132)			61 (134)	

Equipment:

External alternator: 3,0 kg (6,6 lb)

Vacuum pump: 0,8 kg (1,8 lb)

Overload clutch: 1,7 kg (3,7 lb)

◆ **NOTE:** The overload clutch is installed on all certified aircraft engines and on non-certified aircraft engines of the configuration 3.

8.3) Fuel consumption


Fuel consumption in l/h (US gal/h)	912 UL / A F	912 ULS / S
at take-off performance	24,0 (6,3)	27,0 (7,1)
at max. continuous performance	22,6 (5,6)	25,0 (6,6)
at 75% ontinuous performance	16,2 (4,3)	18,5 (4,9)
specific consumption at max. continuous performance	285 g/kWh (0,47 lb/hph)	285 g/kWh (0,47 lb/hph)

8.4) Direction of rotation

Direction of rotation on propeller shaft:counter clockwise,
looking at p.t.o. side of
engine

- ◆ NOTE: Propeller shouldn't be turned reverse the normal direction of engine rotation.

normal direction of propeller rotation (engine)



03646

9) Description of systems

9.1) Cooling system

See fig. 4.

The cooling system of the ROTAX 912 is designed for liquid cooling of the cylinder heads and ram-air cooling of the cylinders. The cooling system of the cylinder heads is a closed circuit with an expansion tank.

The coolant flow is forced by a water pump, driven from the camshaft, from the radiator to the cylinder heads. From the top of the cylinder heads the coolant passes on to the expansion tank (1). Since the standard location of the radiator (2) is below engine level, the expansion tank located on top of the engine allows for coolant expansion.

The expansion tank is closed by a pressure cap (3) (with excess pressure valve and return valve). At temperature rise of the coolant the excess pressure valve opens and the coolant will flow via a hose at atmospheric pressure to the transparent overflow bottle (4). When cooling down, the coolant will be sucked back into the cooling circuit.

◆ **NOTE:** Coolant temperatures are measured by means of temperature probes installed in cylinder heads 2 and 3.

Readings are taken on measuring point of the hottest cylinder head, depending on engine installation.

Coolant, see Chapter 10.2.1).




fig. 4
08111

9.2) Fuel system


See fig. 5.

The fuel flows from the tank (1) via a coarse filter (2) the safety cock (3), water drain cock (4) and fine filter (5) to the mechanical fuel pump (6). From the pump fuel passes on to the two carburetors (7).

Via the return line (8) surplus fuel flows back to the fuel tank.

◆ **NOTE:** The return line serves to avoid formation of vapour lock.

Fuel, see Chapter 10.2.2).



9.3) Lubrication system

See fig. 6.

The ROTAX 912 engine is provided with a dry sump forced lubrication system with a main oil pump with integrated pressure regulator (1) and oil pressure sensor (2).

◆ NOTE: The oil pump is driven by the camshaft.


The oil pump (3) sucks the motor oil from the oil tank (4) via the oil cooler (5) and forces it through the oil filter (6) to the points of lubrication in the engine.

The surplus oil emerging from the points of lubrication accumulates on the bottom of crankcase and is forced back to the oil tank by the blow-by gases.

◆ NOTE: The oil circuit is vented via bore (7) on the oil tank.

◆ NOTE: The oil temperature sensor (8) for reading of the oil inlet temperature is located on the oil pump housing.

Lubricants, see Chapter 10.2.3).



9.4) Electric system

See fig. 7.


The ROTAX 912 engine is equipped with a dual ignition unit of a breakerless, capacitor discharge design, with an integrated generator.

The ignition unit is completely free of maintenance and needs no external power supply.

Two independent charging coils (1) located on the generator stator supply one ignition circuit each. The energy is stored in capacitors of the electronic modules (2). At the moment of ignition each of the 4 external trigger coils (3) actuate the discharge of the capacitors via the primary circuit of the dual ignition coils (4).

Firing order: 1-4-2-3.

◆ NOTE: The 5th trigger coil (5) is planned for rev. counter signal.



9.5) Propeller gearbox


See fig. 8.

For the engine type 912 two reduction ratios are available.

reduction ratio	912 UL / A / F	912 ULS / S
crankshaft: propeller shaft	2,27 : 1	2,43 : 1
	2,43 : 1 (optional)	

Depending on engine type, certification and configuration the propeller gearbox is supplied with or without an overload clutch.

- ◆ **NOTE:** The overload clutch is installed on serial production on all certified aircraft engines and on the non-certified aircraft engines of configuration 3.



- ◆ **NOTE:** Fig. 8 shows a propeller gearbox of configuration 2 with the integrated overload clutch.

The design incorporates a torsional shock absorber. The shock absorbing is based on progressive torsional cushioning due to axial spring load acting on a dog hub.

On the gearbox version with overload clutch the design incorporates a friction damped free play at the dogs to warrant proper engine idling.

Due to this backlash at the dogs a distinct torsional impact arises at start, stop and at sudden load changes, but due to the built-in overload clutch it will remain harmless.

- ◆ **NOTE:** This overload clutch will also prevent any undue load to the crankshaft in case of ground contact of the propeller.

Alternatively **either** a vacuum pump **or** a hydraulic governor for constant speed propeller can be used. The drive is in each case via the propeller reduction gear.

9.5.1) Hydr. governor for const. speed propeller, vacuum pump:

Alternatively **either** a vacuum pump **or** a hydraulic governor for constant speed propeller can be used. The drive is in each case via the propeller reduction gear.

Gear ratio:

gear ratio		
crankshaft : propeller shaft	2,27 : 1	2,43 : 1
propeller shaft : hydraulic governor/vacuum pump	0,758 : 1	
crankshaft : hydraulic governor/vacuum pump	1,724 : 1	1,842 : 1

- ◆ **NOTE:** Transmission ratio between crankshaft and hydraulic governor or vacuum pump is either 1,842 or 1,724 i.e. the speed of the hydraulic governor or vacuum pump is either 0,54 or 0,58 of engine speed.

10) Operating instructions

The data of the certified engines are based on type certificate of type 912 A JAR 22 (TC No. EASA.E.121), 912 F / S FAR 33 (TC No. E00051EN), JAR-E (TC No. EASA.E.121)

10.1) General limits of operation

10.1.1) Operating speeds and limits (912 UL / A / F)

1. Speed:

Take-off speed 5800 1/min (5 min.)
Max. continuous speed 5500 1/min
Idle speed approx. 1400 1/min

2. Performance (ISA): (International Standard Atmosphere)

Take-off performance 59,6 kW at 5800 1/min
Max. continuous performance 58 kW at 5500 1/min

3. Acceleration:

Limit of engine operation at zero gravity and in **negative "g"** condition
max. 5 seconds at max. -0,5 g

4. Oil pressure:

max. 7 bar

■ **CAUTION:** For a short period admissible at cold start.

min. 0,8 bar (12 psi) (below 3500 rpm)
normal 2,0 - 5,0 bar (29 - 73 psi) (above
..... 3500 rpm)

5. Oil temperature:

max. 140 °C (285 °F)
min. 50 °C (120 °F)
normal operating temperature approx. 90 - 110 °C (190 - 230 °F)

6. Coolant

See Operating media Chapter 10.2.1

- In use of conventional coolant:

Coolant temperature: (coolant exit temperature)

max. 120 °C (248 °F)

Cylinder head temperature:

max. 150 °C (300 °F)

Permanent monitoring of coolant temperature and cylinder head temperature is necessary.

- In use of waterless coolant:

Cylinder head temperature:

max. 150 °C (300 °F)

Permanent monitoring of cylinder head temperature is necessary.

7. **Engine start, operating temperature:**
max..... 50 °C (120 °F)
min..... -25 °C (-13 °F)

8. **Fuel pressure:**
max..... 0,4 bar 5,8 psi)
min..... 0,15 bar 2,2 psi)

▲ **WARNING:** Exceeding the max. admissible fuel pressure will override the float valve of the carburetor and to engine failure.

The aircraft engine manufacturer strongly recommends the installation of an additional pump, unless this has not been covered by legal obligations so far.

9. **Power consumption of the hydraulic propeller governor:**
max..... 600 W

10. **Power consumption of the vacuum pump:**
max..... 300 W

11. **Power consumption of the external alternator:**
max..... 1200 W

12. **Deviation from bank angle**
max..... 40°

◆ **NOTE:** Up to this value the dry sump lubrication system warrants lubrication in every flight situation.

10.1.1.1) Performance graphs for stand. conditions (ISA)

00450

A: max. engine output
B: power requirement of propeller




fig. 9

00451

C: manifold pressure
D: fuel consumption




fig. 10

d03934.fm

Performance data for variable pitch propeller:

Engine operation is permitted without restriction between full throttle performance and power requirement of propeller, providing engine speed over 5500 r.p.m. is restricted to 5 minutes.


However, for economic reasons it is recommended to run the engine in accordance with the following table:

Engine Power-Setting	Engine speed [rpm]	Performance [kW]	Torque [Nm]	Manifold pres. [in.HG]
Take-off perform.	5800	59,6	98,1	full throttle
cruising power	5500	58,0	100,7	full throttle
75%	5000	43,5	83,1	27,2
65%	4800	37,7	75,0	26,5
55%	4300	31,9	70,8	26,3

10.1.1.2) Performance graph for non-standard conditions

The following graph shows the performance drop with increasing flight altitude. The curves show the performance at 5800, 5500, 5000, 4500 and 4000 r.p.m., at full throttle.

The engine allows operation with fully open throttle valve over the whole r.p.m. range, without limitation. But full throttle performance above 5500 r.p.m. is limited to 5 minutes.



At deviation of temperature conditions from standard atmosphere conditions the engine performance to be expected can be calculated from the performance indicated, multiplied by standard temperature, divided by actual temperature in °K.

$$P_{\text{akt.}} = P_{\text{stand.}} \cdot \frac{T_{\text{standard}}}{T_{\text{aktuell}}}$$

$$T[\text{K}] = t[^\circ\text{C}] + 273$$

00452

fig. 11

d03934.fm

10.1.2) Operating speeds and limits (912 ULS / S)

1. Speed:

Take-off speed 5800 1/min (5 min.)
Max. continuous speed 5500 1/min
Idle speed approx. 1400 1/min

2. Performance (ISA): (International Standard Atmosphere)

Take-off performance 73,5 kW at 5800 1/min
Max. continuous performance 69 kW at 5500 1/min

3. Acceleration:

Limit of engine operation at zero gravity and in **negative "g"** conditions

max. 5 seconds at max. -0,5 g

4. Oil pressure:

max. 7 bar

■ **CAUTION:** For a short period admissible at cold start.

min. 0,8 bar (12 psi) (below 3500 rpm)
normal 2,0 - 5,0 bar (29 - 73 psi) (above 3500 rpm)

5. Oil temperature:

max. 130 °C (266 °F)
min. 50 °C (120 °F)
normal operating temperature approx. 90 - 110 °C (190 - 230 °F)

6. Coolant:

See Operating media Chapter 10.2.1

- In use of conventional coolant:

Coolant temperature: (coolant exit temperature)

max. 120 °C (248 °F)

Cylinder head temperature:

max. 135 °C (275 °F)

Permanent monitoring of coolant temperature and cylinder head temperature is necessary.

- In use of waterless coolant:

Cylinder head temperature:

max. 135 °C (275 °F)

Permanent monitoring of cylinder head temperature is necessary.

7. Engine start, operating temperature:

max. 50 °C (120 °F)
min. - 25 °C (- 13 °F)

8. Fuel pressure:

max.....0,4 bar (5,8 psi)

min.....0,15 bar (2,2 psi)

▲ **WARNING:** Exceeding the max. admissible fuel pressure will override the float valve of the carburetor and to engine failure.

The aircraft engine manufacturer strongly recommends the installation of an additional pump, unless this has not been covered by legal obligations so far.

9. Power consumption of the hydraulic propeller governor:

max.....600 W

10. Power consumption of the vacuum pump:

max.....300 W

11. Power consumption of the external alternator:

max.....1200 W

12. Deviation from bank angle

max.....40°

◆ **NOTE:** Up to this value the dry sump lubrication system warrants lubrication in every flight situation.

10.1.2.1) Performance graphs for stand. conditions (ISA)




fig. 12

02001




fig. 13

02002

d03934.fm

Performance data for variable pitch propeller:

Engine operation is permitted without restriction between full throttle performance and power requirement of propeller, providing engine speed over 5500 r.p.m. is restricted to 5 minutes.

However, for economic reasons it is recommended to run the engine in accordance with the following table:


Engine Power-Setting	Engine speed [rpm]	Performance [kW]	Torque [Nm]	Manifold pres. [in.HG]
Take-off perform.	5800	73,5	121,0	27,5
cruising power	5500	69,0	119,8	27
75%	5000	51,0	97,4	26
65%	4800	44,6	88,7	26
55%	4300	38,0	84,3	24

10.1.2.2) Performance graph for non-standard conditions

The following graph shows the performance drop with increasing flight altitude. The curves show the performance at 5800, 5500, 5000, 4800 and 4300 r.p.m., at full throttle.

The engine allows operation with fully open throttle valve over the whole r.p.m. range, without limitation. But full throttle performance above 5500 r.p.m. is limited to 5 minutes.

At deviation of temperature conditions from standard atmosphere conditions the engine performance to be expected can be calculated from the performance indicated, multiplied by standard temperature, divided by actual temperature in °K.



$$P_{\text{akt.}} = P_{\text{stand.}} \cdot \frac{T_{\text{standard}}}{T_{\text{aktuell}}}$$

$$T[\text{K}] = t [^{\circ}\text{C}] + 273$$

fig. 14

05482

10.2) Operating media

10.2.1) Coolant

In principle, 2 different types of coolant are permitted.

- Conventional coolant based on ethylene glycol
- Waterless coolant based on propylene glycol

■ **CAUTION:** Obey the manufacturer's instructions about the coolant.

designation	mixture ratio %	
	concentrate	water
conventional e.g. BASF Glysantine anticorrosion	50	50
waterless e.g. EVANS NPG+	100	0

Conventional coolant mixed with water has the advantage of a higher specific thermal capacity than water-less coolant.

◆ **NOTE:** The important advantage of water-less coolant is its higher boiling point than a conventional mixture.

When correctly applied, there is sufficient protection against vapor bubble formation, freezing or thickening of the coolant within the operating limits.

Use the coolant specified in the manufacturer's documentation.

■ **CAUTION:** Obey the latest edition of Service Instruction SI-912-016 for the selection of the correct coolant.

10.2.2) Fuel

The following fuels can be used :

			Usage / Description	
			912 UL / A / F	912 ULS / S
MOGAS				
European standard	EN 228 Normal ¹⁾			
	EN 228 Super ¹⁾		EN 228 Super ²⁾	
	EN 228 Super plus ¹⁾		EN 228 Super plus ²⁾	
Canadian standard	CAN/CGSB3.5 Quality 1 ³⁾		CAN/CGSB3.5 Quality 3 ⁴⁾	
US standard	ASTM D4814		ASTM D4814	
AVGAS				
US standard	AVGAS 100 LL (ASTM D910)		AVGAS 100 LL (ASTM D910)	

¹⁾ min. ROZ 90

²⁾ min. ROZ 95

³⁾ min. AKI* 87

⁴⁾ min. AKI 91

AVGAS 100LL places greater stress on the valve seats due to its high lead content and forms increased deposits in the combustion chamber and lead sediments in the oil system. Thus it should only be used in case of problems with vapor lock or when other types of gasoline are unavailable.

- CAUTION: Use only fuel suitable for the respective climatic zone.
- ◆ NOTE: Risk of vapour formation if using winter fuel for summer operation.
- CAUTION: Obey the latest edition of Service Instruction SI-912-016 for the selection of the correct fuel.

d03934.fm

10.2.3) Lubricants

Oil: Motorcycle oil of a registered brand with gear additives. If using aircraft engine oil; than only blended one.

- CAUTION: At the selection of suitable lubricants refer to the additional information in the Service Information SI-912-016, latest edition.

Oil specification

- Use only oil with API classification "**SG**" or higher!
 - Due to the high stresses in the reduction gears, oils with gear additives such as high performance motor cycle oils are required.
 - Because of the incorporated friction clutch, oils with friction modifier additives are unsuitable as this could result in a slipping clutch during normal operation.
 - Heavy duty 4-stroke motor cycle oils meet all the requirements. These oils are normally no mineral oils but semi- or full synthetic oils.
 - Oils primary for Diesel engines are due to **insufficient high temperature properties and additives which favour clutch slipping, generally unsuitable.**
- CAUTION: If the engine is mainly run on AVGAS **more frequent** oil changes will be required. See Service Information SI-912-016, latest edition.

Oil consumption: max 0,06 l/h (0.13 liq pt/h)

Oil viscosity:

Use of multi-grade oils is recommended.

- ◆ **NOTE:** Multi-viscosity grade oils are less sensitive to temperature variations than single grade oils. They are suitable for use throughout the seasons, ensure rapid lubrication of all engine components at cold start and get less fluid at higher temperatures.

Table of lubricants (See fig. 15)

Since the temperature range of neighboring SAE grades overlap, there is no need for change of oil viscosity at short duration of ambient temperature fluctuations.




fig. 15

01176

d03934.fm

10.3) Standard operation

To warrant reliability and efficiency of the engine, meet and carefully observe all the operating and maintenance instructions.

10.3.1) Daily checks

- ▲ **WARNING:** **Risk of burnings and scalds!**
Conduct checks on the cold engine only!

- ▲ **WARNING:** **Ignition "OFF".** Before cranking the propeller switch off both ignition circuits and anchor the aircraft. Have the cockpit occupied by a competent person.

- **CAUTION:** If established abnormalities (e.g. excessive resistance of the engine, noises etc.) inspection in accordance with the relevant Maintenance Manual is necessary. Do not release the engine into service before rectification.

Coolant level:

- **CAUTION:** The coolant specifications of the section 10.2) Operating media are to be observed.

- Verify coolant level in the **expansion tank**, replenish as required up to top.
The coolant level must be at least 2/3 of the expansion tank.

- Verify coolant level in the **overflow bottle**, replenish as required.
The coolant level must be between max. and min. mark or at least 0.2 litre (0.4 liq pt).

Check of mechanical components:

Turn propeller by hand in direction of engine rotation several times and observe engine for odd noises or excessive resistance and normal compression.

Gear box:

- Version without overload clutch:

No further checks are necessary.

- Version with overload clutch:

Turn the propeller by hand to and fro, feeling the free rotation of 15° or 30° before the crankshaft starts to rotate.

If the propeller can be turned between the dogs with practically **no friction** at all (less than 25 Nm = 222 in.lb) further investigation is necessary.

Carburetor:

- Verify free movement of throttle cable and starting carburetor over the complete range. Check from the cockpit.

Exhaust system:

- Inspect for damages, leakage and general condition.

10.3.2) Before engine start

Carry out pre-flight checks.

10.3.3) Pre-flight checks

- ▲ **WARNING:** **Ignition "OFF"** Before cranking the propeller switch off both ignition circuits and anchor the aircraft. Have the cockpit occupied by a competent person.

Operating media:

- ▲ **WARNING:** Carry out pre-flight checks on the cold or luke warm engine only! **Risk of burning and scalds.**

Check for any oil-, coolant- and fuel leaks.

If leaks are evident, rectify before flight.

- **CAUTION:** The coolant specifications of the section 10.2) Operating media are to be observed.

- Verify coolant level in the **overflow bottle**, replenish as required up to top.

The coolant level must be between min. and max. mark or at least 0.2 litre (0.4 liq pt).

- **CAUTION:** The oil specifications of the section 10.2) Operating media are to be observed.

- Check oil level and replenish as required.

- ◆ **NOTE:** Propeller shouldn't be turned reverse the normal direction of engine rotation.

- Prior to oil check, turn the propeller by hand in direction of engine rotation several times to pump oil from the engine into the oil tank, or let the engine idle for 1 minute.

It is essential to build up compression in the combustion chamber. Maintain the pressure for a few seconds to let the gas flow via the piston rings into the crankcase. The speed of rotation is not important as the pressure and the amount of gas which is transferred into the crankcase.

This process is finished when air is returning back to the oil tank and can be noticed by a murmur from the open oil tank.

- ◆ **NOTE:** The oil level should be in the upper half (between the "50%" and the "max" mark) and should never falls below the "min" mark. Prior to long flights oil should be added so that the oil level reaches the "max" mark.

Avoid oil levels exceeding the "max" mark, since excess oil could be poured out through the venting system.

Difference between max.- and min.- mark = 0.45 litre (0.95 liq pt)

10.3.4) Engine start

- ▲ **WARNING:** Do not take the engine into operation if any person is near the aircraft.

Fuel cock..... open

Starting carb. activated

- ◆ **NOTE:** If the engine is already in operating temperature, start the engine without choke.

Throttle lever. set to idle position

Master switch. on

Ignition. both circuits switched on

Starter button. actuate

- **CAUTION:** Activate starter for max. 10 sec. only (without interruption), followed by a cooling period of 2 minutes!

As soon as engine runs, adjust throttle to achieve smooth running at approx. 2500 r.p.m.

Check if oil pressure has risen within 10 seconds and monitor oil pressure. Increase of engine speed is only permitted at steady oil pressure readings above 2 bar (30 psi).

At an engine start with low oil temperature, continue to observe the oil pressure as it could drop again due to the increased flow resistance in the suction line. The number of revolutions may be only so far increased that the oil pressure remains steady.

De-activate starting carb.

- **CAUTION:** Since the engine comprises a reduction gear with shock absorber, take special care of the following:

To prevent impact load, start with throttle lever in idle position or at the most up to 10% open. For the same reason, wait for around 3 sec. after throttling back to partial load to reach constant speed before re-acceleration.

For checking the two ignition circuits, only one circuit may be switched off and on at times.

- **CAUTION:** Do not actuate starter button (switch) as long as the engine is running. Wait until complete stop of engine!

d03934.fm

10.3.5) Prior to take-off

Warming up period:

Start warming up period at 2000 r.p.m. for approx. 2 minutes, continue at 2500 r.p.m., duration depending on ambient temperature, until oil temperature reaches 50 °C (120 °F).

- Check temperatures and pressures.

Throttle response:

- Short full throttle ground test (consult Aircraft Operator's Manual since engine speed depends on the propeller used).

- **CAUTION:** After a full-load ground test allow a short cooling run to prevent vapour formation in the cylinder head.

Ignition check:

Check the two ignition circuits at **4000 r.p.m.** (approx. 1700 r.p.m. propeller).

- Speed drop with only one ignition circuit must not exceed **300 r.p.m.** (approx. 130 r.p.m. propeller).
- **115 r.p.m.** (approx. 50 r.p.m. propeller) max. difference of speed by use of either circuit, A or B.

- ◆ **NOTE:** The propeller speed depends on the actual reduction ratio.

Check of hydraulic propeller governor:

Check control of the hydraulic propeller governor to specifications of the manufacturer.

10.3.6) Take-off

Climbing with engine running at take-off performance is permissible (max. 5 minutes). See Chapter 10.1), 10.1.1) and 10.1.2).

- ▲ **WARNING:** Monitor oil temperature, cylinder head temperature and oil pressure. Limits must not be exceeded! See Chapter 10.1) Operating Limits.
- **CAUTION:** Respect "cold weather operation" recommendations, see Chapter 10.3.9).

10.3.7) Cruising

Set performance as per performance specifications and respect operating limits as per Chapter 10.1), 10.1.1) and 10.1.2).

Avoid operation below normal operation oil temperature (90 - 110 °C / 194 - 230 °F), as possible formation of condensation water in the lubrication system badly influences the oil quality.

To evaporate possibly accumulated condensation water, at least once a day 100 °C (212 °F) oil temperature must be reached.

10.3.8) Engine shut-off

Normally the cooling down of the engine during descending and taxiing will be sufficient to allow the engine to be shut off as soon as the aircraft is stopped.

At increased operating temperatures to make an engine cooling run of at minimum 2 minutes.

10.3.9) Cold weather operation

Generally, an engine service should be carried out before the start of the cold season.

Coolant:

For selection of coolant and mixing ratio, see "Coolant", Chapter 10.2.1).

Lubricant:

For selection of oil, see Table of Lubricants (Chapter 10.2.3).

Cold start:

- With throttle closed and choke activated (open throttle renders starting carb ineffective).
- Be aware, no spark below crankshaft speed of 220 rpm. (propeller speed of 90 rpm.).
- As performance of electric starter is greatly reduced when hot, limit starting to periods not much longer than 10 sec. With a well charged battery, adding a second battery will not improve cold starts.

Remedy:

- Use of multigrade oil with the low end viscosity code of 5 or 10.
- Gap electrode on spark plug to the minimum or fit new spark plugs.

d03934.fm

- Preheat engine using hot air.

Beyond that observe following advices for operation at extremely low temperatures:

- ◆ **NOTE:** Distinguish between two kinds of carb icing:
 - 1) Icing due to water in fuel
 - 2) Icing because of high air humidity

Addendum to note 1)

Water in fuel will accumulate at the lower parts of the fuel system and leads to freezing of fuel lines, filters or jets.

Remedy:

- Use non-contaminated fuel (filtered through suède)
- Generously sized water separators
- Fuel lines routing inclined
- Prevent condensation of humidity, i.e. avoid temperature differences between aircraft and fuel.

- ▲ **WARNING:** Fuels containing alcohol always carry a small amount of water in solution. In case of temperature changes or increase of alcohol content, water or a mixture of alcohol and water may settle and could cause troubles.

Addendum to note 2)

Carburetor icing due to humidity may occur on the venturi and on the throttle valve due to fuel evaporation and leads to performance loss and change in mixture. Intake air pre-heating is the only effective remedy.

10.4) Abnormal operation

▲ **WARNING:** At unusual engine behaviour conduct checks as per Chapter 10.4.1) through 10.4.13) below, and as per Maintenance Manual, Chapter 05) before the next flight.

◆ **NOTE:** Further checks - see Maintenance Manual.

10.4.1) Engine stop - Start during flight

Starting procedure same as on ground, however, on a warm engine without choke.

10.4.2) Exceeding of max. admissible engine speed

Reduce engine speed. Any exceeding of the max. admissible engine speed has to be entered by the pilot into the logbook, stating duration and extent of overspeed.

10.4.3) Exceeding of max. admissible cyl. head temperature

▲ **WARNING:** Reduce engine power setting to the minimum necessary and carry out precautionary landing.

Any exceeding of the max. admissible cylinder head temperature has to be entered by the pilot into the logbook, stating duration and extent of over-temperature condition.

10.4.4) Exceeding of max. admissible oil temperature

▲ **WARNING:** Reduce engine power setting to the minimum necessary and carry out precautionary landing.

Any exceeding of the max. oil temperature must be entered by the pilot in the logbook, stating duration and extent of over-temperature condition.

10.4.5) Oil pressure below minimum - during flight

▲ **WARNING:** Reduce engine power setting to the minimum necessary and carry out precautionary landing.

Check oil system.

10.4.6) Oil pressure below minimum - on ground

Immediately stop the engine and check for reason. Check oil system.

- Check oil quantity in oil tank.
- Check oil quality (see section 10.2.3).

d03934.fm

11) Checks

All checks to be carried out as specified in the current Maintenance Manual (last revision).

- ▲ **WARNING:** **Only qualified staff (authorized by the Aviation Authorities) trained on this particular engine, is allowed to carry out maintenance and repair work.**
- **CAUTION:** Carry out all directives of Service Bulletins (SB), according to their **priority**.

11.1) Engine preservation

Due to the special material of the cylinder wall, there is no need for extra protection against corrosion. At extreme climatic conditions and for long out of service periods we recommend the following to protect the valve guides against corrosion:

- Let engine run until warm, then change oil.
- Remove the air intake filters and insert approx. 30 cm³ (1 fl oz) of corrosion inhibiting oil into the carburetor throat with the engine running at increased idle speed. Shut off engine.
- Drain carburetor float chamber.
- Apply oil to all joints on carburetors.
- Close **all** openings on the cold engine, such as exhaust end pipe, venting tube, air filter etc. against entry of dirt and humidity.
- Spray all steel external engine parts with corrosion inhibiting oil.

Engine back to operation

- Remove all plugs and fasteners.
- Clean spark plugs with plastic brush and solvent.
- If preservation including oil change took place within a year of storage, oil renewal will not be necessary. For longer storage periods repeat preservation annually.

NOTES

12) Trouble shooting

- ▲ **WARNING:** Only qualified staff (authorized by the Aviation Authorities) trained on this particular engine, is allowed to carry out maintenance and repair work.

If the following hints regarding remedy do not solve the problem, contact an authorized workshop. The engine must not be operated until the problem is rectified.

Engine does not start

POSSIBLE CAUSE:

- a - ignition off
- b - closed fuel tap or clogged filter
- c - no fuel in tank
- d - starting speed too low, faulty or discharged battery
- e - starting speed too low, start problems on cold engine

REMEDY:

- switch on.
- open tap, clean or renew filter, check fuel system for leaks.
- refuel.
- fit fully charged battery.
- use top quality, low friction oil; allow for sufficient cooling period to counter for performance drop on hot starter; pre-heat engine.

Engine idles rough after warm-up period, smoky exhaust emission

POSSIBLE CAUSE:

- a - starting carb activated

REMEDY:

- close starting carb.

Low oil pressure

POSSIBLE CAUSE:

- a - not enough oil in oil tank

REMEDY:

- check oil return line for free passage, renew oil seal.

Engine keeps running with ignition off

POSSIBLE CAUSE:

- a - overheating of engine

REMEDY:

let engine cool down at idling at approx. 2000 r.p.m.

Oil level is increasing

POSSIBLE CAUSE:

- a - oil too cold during engine operation

REMEDY:

cover oil cooler surface, maintain the oil temperature prescribed.

Knocking under load

POSSIBLE CAUSE:

- a - Octane rating of fuel too low

REMEDY:

use fuel with higher octane rating.

Engine hard to start at low temperature

POSSIBLE CAUSE:

- a - starting speed too low
- b - low charge battery
- c - high oil pressure
- d - oil pressure too low after cold start

REMEDY:

preheat engine.

fit fully charged battery.

at cold start a pressure reading of up to around 7 bar (102 psi) does not indicate a malfunction.

too much resistance in the oil suction tube at low temperatures. Stop engine and preheat oil.

At oil pressure reading too low than 1 bar oils with lower viscosity are to be used.

See SI-912-016, current issue.

◆ NOTE:

Oil pressure must in the idle operation with an oil temperature of min. 50 °C (120°F) to be measured.

NOTES


12.1) Reporting

According to the regulation of JAR / FAR 21.3 the manufacturer shall evaluate field information and report to the authority. In case of any relevant occurrences that may involve malfunction of the engine, the form on the next page should be filled out and sent to the responsible authorized ROTAX distributor.

- ◆ NOTE: The form is also available from the official ROTAX AIRCRAFT ENGINES Homepage

www.rotax-aircraft-engines.com

in electronic version.

		OPER. Control No.		SERIAL NUMBER	
		ATA Code		MODEL/SERIES	
1. A/C Reg. No.		MANUFACTURER		SERIAL NUMBER	
2. AIRCRAFT		MANUFACTURER		SERIAL NUMBER	
3. POWERPLANT		ROTAX		SERIAL NUMBER	
4. PROPELLER		MANUFACTURER		SERIAL NUMBER	
5. SPECIFIC PART (of component) CAUSING TROUBLE					
Part Name		MFG. Model or Part No.		Serial No.	
Part/Defect Location		MFG. Model or Part No.		Serial No.	
6. ENGINE COMPONENT (Assembly that includes part)					
Engine/Comp. Name		Manufacturer		Model or Part No.	
Engine TSN		Engine TSO		Engine Condition	
Date Sub.		Date Sub.		Date Sub.	

8. Comments (Describe the malfunction or defect and the circumstances under which it occurred. State probable cause and recommendations to prevent recurrence.)

OPERATOR DESIGNATOR	SUBMITTED BY:						
DISTRICT OFFICE	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
OTHER	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
ACG	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
MFG	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
AIR TAXI	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
MECH	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
OPER	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
REP. STA	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

TELEPHONE NUMBER: () —

Optional Information:

Check a box below, if this report is related to an aircraft

Accident; Date

Incident; Date

NOTES

1) EUROPE

AUSTRIA:

► **HB - FLUGTECHNIK GMBH**
Dr. Adolf Schärf Str. 42
A-4053 HAID
Tel.: +43 (0)7229 / 79104,
Fax: +43 (0) 7229 / 79104 15
E-mail: info@hb-flugtechnik.at
Website: www.hb-flugtechnik.at
Contact person: Ing. Heino Brditschka

BULGARIA:

► **GERGANOV - AIRCRAFT ENGINES LTD.**
25B-Post 20, 23 peh. Shlp. polk Blvd.
BG-6100 KAZANLAK
Tel.: +359 (0) 431 / 27 247,
Fax: +359 (0) 431 / 23 777
E-mail: gaerotax@mbox.contact.bg
Contact person: Radosslav D. Gerganov

**CROATIA / FORMER YUGOSLAVIA
(EXEPT SLOVENIA):**

► **SHAFT D.O.O.**
B.L. Mandica 161 a
HR-54000 OSIJEK
Tel. +385 (0) 31 /280-046,
Fax: +385 (0) 31 /281-602
E-mail: shaft@os.tel.hr
Contact person: Ing. Ivan Vdovjak

CZECHIA:

► **TEVESO S.R.O.**
Skroupova 441
CS-50002 HRADEC KRALOVE
Tel.: +42 (0) 49 / 5217 127,
Fax: +42 (0) 49 / 5217 226
E-mail: motory@teveso.cz
Website: www.teveso.cz
Contact person: Ing. Jiri Samal

**SWEDEN / FINLAND / NORWAY /
ESTONIA / LATVIA / LITHUANIA /
DENMARK**

► **LYCON ENGINEERING AB**
Härkeberga, SE-74596 ENKÖPING
Tel.: +46 (0) 171 / 414039,
Fax: +46 (0) 171 / 414116
E-mail: info@lycon.se
Website: www.lycon.se

**FRANCE / BELGIUM / MONACO /
LUXEMBURG:**

► **MOTEUR AERO DISTRIBUTION**
11 Blvd Albert 1
98000 MONACO
Tel.: +377 (0) 93 30 17 40,
Fax: +377 (0) 93 30 17 60
E-mail: mad@libello.com
Website: www.moteuraerodistribution.com
Contact person: Philippe Thys

GERMANY / THE NETHERLANDS:

► **FLUGMOTOREN FRANZ GMBH**
Am Weidengrund 1a, 83135 Schechen, Germany
Tel.: +49 (0) 8039 / 90350,
Fax: +49 (0) 8039 / 9035-35
E-mail: info@franz-aircraft.de
Website: www.franz-aircraft.de
Contact person: Eduard Franz

**GREAT BRITAIN / IRELAND /
ICELAND:**

► **SKYDRIVE LTD.**
Burnside, Deppers Bridge
SOUTHAM, WARWICKSHIRE CV47 2SU
Tel.: +44 (0) 1926 / 612 188,
Fax: +44 (0) 1926 / 613 781
E-mail: sales@skydrive.co.uk
Website: www.skydrive.co.uk
Contact person: Nigel Beale

HUNGARY:

► **HALLEY**
Baktai út 45, P.O. Box 425
H-3300 EGER
Tel.: +36 (0) 36 / 313-830,
Fax: +36 (0) 36 / 320-208
E-mail: apollo@mail.datanet.hu
Contact person: Zoltán Molnár

ITALY:

► **LUCIANO SORLINI S.P.A.**
Piazza Roma, 1
Carzago di Calvagese Riviera (Brescia), Italy
Tel.: +39 030 / 601 033,
Fax: +39 030 / 601 463
E-mail: avio@sorlini.com
Website: www.sorlini.com
Contact person: Alberto Comincioli

POLAND:

► **FASTON LTD.**
ul. Zwirki i Wigury 47
PL-21-040 SWIDNIK
Tel.: +48 (0) 81 / 751-2882;
Fax: +48 (0) 81 / 751-5740
E-mail: faston@go2.pl
Contact person: Mariusz Oltarzewski

ROMANIA:

► **S.C. BERIMPEX S.R.L.**
Str. Dr. Taranu Grigore No. 8, Ap. 2, Sector 5
R-76241 BUCHAREST
Tel.: +40 (0) 21 / 410 90 03;
Fax: +40 (0) 21 / 410 9020
E-mail: berimpex@clicknet.ro
Contact person: Dr. Cristian Berar

SLOVAKIA:

►TEVESO S.R.O.

Skroupova 441
CS-50002 HRADEC KRALOVE
Tel.: +42 (0) 49 / 5217 127,
Fax: +42 (0)49 / 5217 226
E-mail: motory@teveso.cz
Website: www.teveso.cz
Contact person: Ing. Jiri Samal

SLOVENIA:

►PIPISTREL D.O.O.

Goriska Cesta 50A
5270 AJDOVSCINA
Tel. +386 (0) 5 / 3663 873,
Fax: +386 (0) 5 / 3661 263
E-mail: pipistrel@siol.net
Website: www.pipistrel.si
Contact person: Ivo Boscarol

SPAIN / PORTUGAL:

►AVIASPORT S.A.

Almazara 11
E-28760 TRES CANTOS (MADRID)
Tel.: +34 (0) 91 / 803 77 11,
Fax: +34 (0) 91 / 803 55 22
E-mail: aviasport@aviasport.com
Website: www.aviasport.com
Contact person: Roberto Jimenez

SWITZERLAND / LIECHTENSTEIN:

►FRANZ AIRCRAFT ENGINES VERTRIEB GMBH

Am Weidengrund 1a, 83135 Schechen,
GERMANY
Tel.: +49 (0) 8039 / 90350,
Fax: +49 (0) 8039 / 9035-35
E-mail: info@franz-aircraft.de
Website: www.franz-aircraft.de
Contact person: Eduard Franz

TURKEY:

►AIR CONSULT

Belediye Evler Mah., 368. Sk., Vilko Sitesi No. 8
01360 Adana-Kurttepe TURKEY
Tel.: +90 (0) 322 / 248 0746;
Fax: +90 (0) 322 / 248 6927
E-Mail: sales@airconsult.com
Contact person: Peter Girmann

2. A M E R I C A

CANADA:

►ROTECH RESEARCH CANADA, LTD.

6235 Okanagan Landing Rd.
VERNON, B.C., V1H 1M5, CANADA
Tel.: +1 250 / 260-6299,
Fax: +1 250 / 260-6269
E-mail: inquiries@rotec.com
Website: www.rotec.com

NORTH / MIDDLE / SOUTH

AMERICA:

►KODIAK RESEARCH LTD.

PO N 658
Bay & Deveaux Street
NASSAU, BAHAMAS
Tel.: +1 242 / 356 5377,
Fax: +1 242 356 2409
E-mail: custsupport@kodiakbs.com
Website: www.kodiakbs.com

3) A U S T R A L I A /

N E W Z E A L A N D /

P A P U A N E W G U I N E A

►BERT FLOOD IMPORTS PTY. LTD.

P.O. Box 61, 16-17 Chris Drive
LILYDALE, VICTORIA 3140
Tel.: +61 (0) 3 / 9735 5655,
Fax: +61 (0) 3 / 9735 5699
E-mail: wal@bertfloodimports.com.au
Website: www.bertfloodimports.com.au
Contact person: Mark Lester

4) AFRICA

EGYPT:

►AL MOALLA

P.O. Box 7787, ABU DHABI
Tel.: +971 (0) 2 / 444 7378,
Fax: +971 (0) 2 / 444 6896
E-mail: almoalla@emirates.net.ae
Contact person: Hussain Al Moalla

ANGOLA / BOTSWANA / LESOTHO/

MADAGASCAR / MALAWI /

MOZAMBIQUE/ NAMIBIA / SOUTH

AFRICA / SWAZILAND/ ZAMBIA /

ZIMBABWE:

►AVIATION ENGINES AND ACCESSO- RIES (PTY) LTD

Private Bag X10021, Edenvale 1610,
SOUTH AFRICA
Tel.: +27 (0) 11 / 455 4203, Fax: +27 (0) 11 / 455 4499
E-mail: niren@aviation-engines.co.za
Website: www.aviation-engines.co.za
Contact person: Niren Chotoki

**GHANA / BENIN / BURKINA FASO /
CAMEROON / CENTRAL AFRICAN
REPUBLIC / CONGO / GABON / GUINEA
/ IVORY COAST / MALI / MAURITANIA
/ NIGER/ NIGERIA / SENEGAL / TOGO:**

► **WAASPS LTD**

PMB KA49, Kotoka International Airport, Accra,
GHANA
Tel.: +233 (0) 28 5075254,
Fax: +233 (0) 217 717 92
E-mail: info@waasps.com
Website: www.waasps.com
Contact person: Jonathan Porter

5) ASIA

CHINA / HONG KONG / MACAO:

► **PEIPORT INDUSTRIES LIMITED.**

Rm. 1302, Westlands Centre
20 Westlands Road, Quarry Bay
HONG KONG
Tel.: +852 (0) 2885 / 9525,
Fax: +852 (0) 2886 / 3241
E-mail: admin@peiport.com.hk
Website: www.peiport.com
Contact person: Larry Yeung

CIS:

► **AVIAGAMMA JSCO.**

P.O. Box 51, 125 057 MOSCOW
Tel.: +7 499 / 158 31 23,
Fax: +7 499 / 158 62 22
E-mail: aviagamma@mtu-net.ru
Website: www.aviagamma.ru
Contact person: Vladimir Andriytschuk
General Director

INDIA:

► **GREAVES COTTON LTD.**

Express Building Annexe
9-10, Bahadur Shah Zafar Marg
NEW DELHI - 110 002
Tel.: +91 (0) 11 / 23311501
Fax: +91 (0) 11 / 23702129
E-mail: anilkumar@greavesmail.com
Website: www.greavescotton.com/aeroengines.htm
Contact person: Cdr. Anil Kumar
Divisional Manager

**INDONESIA / MALAYSIA / PHILIP-
PINES / SINGAPORE / THAILAND /
TAIWAN:**

► **BERT FLOOD IMPORTS PTY. LTD**

P.O. Box 61, 16-17 Chris Drive LILYDALE,
VICTORIA 3140
Tel.: +61 (0) 3 / 9735 5655,
Fax: +61 (0) 3 / 9735 5699
E-mail: wal@bertfloodimports.com.au
Website: www.bertfloodimports.com.au
Contact person: Mark Lester

IRAN:

► **ASEMAM PISHRANEH CO.**

13 Km of Babae Exp. Way, Cross Telo Road,
Sepehr Aviation Group, Tehran, Iran
Tel.: +98 (0) 21 77105107,
Fax: +98 (0) 21 77000030
E-mail: asmpish@asmpish.com
Contact person: Ali Habibi Najafi

ISRAEL:

► **CONDOR-AVIATION
INDUSTRIES LTD.**

P.O. Box 1903, 14 Topaz st.
Cesaria 38900
Tel.: +972 (0) 4 / 6265080,
Fax: +972 (0) 4 / 62650 95
E-mail: condor@netvision.net.il
Contact person: David Wiernik

JAPAN :

► **JUA, LTD.**

1793 Fukazawa, Gotemba City
SHIZUOKA PREF 412
Tel.: +81 (0) 550 / 83 8860,
Fax: +81 (0) 550 / 83 8224
E-mail: jua@shizuokanet.ne.jp
Contact person: Yoshihiko Tajika,
President

KOREA:

► **KORBER IND. CO. LTD.**

#1104, Biz Center, SK Technopark, 190-1
Sangdeawon-Dong, Joongwon-Ku,
Seoungnam City, SOUTH KOREA
Tel.: +82 (0) 31 / 776 0771/5
Fax: +82 (0) 31 / 776 0776
E-mail: johnlee@korberco.com
Contact person: John Lee, President

UNITED ARAB. EMIRATES:

► **AL MOALLA**

P.O. Box 7787
ABU DHABI
Tel.: +971 (0) 2 / 444 7378
Fax: +971 (0) 2 / 444 6896
E-mail: almoalla@emirates.net.ae
Contact person: Hussain Al Moalla

NOTES



Motornummer / Engine serial no.

Flugzeugtype / Type of aircraft

Flugzeugkennzeichen / Aircraft registration no.

ROTAX[®] Vertriebspartner

ROTAX[®] authorized distributor

www.rotax-aircraft-engines.com